

# STEEL ROLLING WAREHOUSE LADDER INSTRUCTIONS



## DANGER

**Metal ladders conduct electricity. Do not use where contact may be made with live electrical circuits. Failure to read and follow instructions on the use of this product could result in serious personal injury or death.**

### Proper Selection

1. Steel warehouse ladders are capable of supporting up to 350 lbs. combined weight of user and materials. Ladders are designed for one person only. Do not overload.
2. Select ladder of proper size to safely reach desired height.

### Inspection Before Each Use

1. Inspect thoroughly for missing or damaged components. Never use a damaged ladder and never make temporary repairs.
2. Inspect thoroughly for loose fasteners. Make sure all working parts are in good working order (lubricate if necessary). Make sure locking device functions properly and all casters operate freely. Replace worn or missing rubber feet and casters.
3. Clean ladder of all foreign material (wet paint, mud, snow, grease, oil, etc.).
4. Destroy ladder if damaged, worn, or deteriorated in any way.

### Consider Before Each Use

1. Metal ladders conduct electricity. Keep away from electrical circuits.
2. Use ladder only as outlined in instructions. Use on firm level surface.
3. Handrails are required on 5 step ladders and larger, toeboard on 12 step ladders and larger.
4. Do not use if in poor health, if taking drugs or alcoholic beverages, or if physically handicapped.

5. Wear slip-resistant shoes. Keep shoes clean. Do not wear shoes with leather soles or high heels.
6. Never leave ladder set up and unattended.
7. Pay close attention to what you are doing.


### Proper Set Up And Use

1. Assemble ladder following directions on separate instruction sheet.
2. Roll ladder into position for access to materials. Keep body centered between handrails. Do not over reach, push, pull, etc. in any way that causes ladder feet or casters to lift off the floor. Climb down to ground and move ladder as needed.
3. On models with spring loaded casters, step on bottom step to engage slip-resistant feet.
4. Before using a ladder with a locking device, step on bottom step to lock ladder in place.
5. Face ladder when climbing up or down, unless approved for forward facing descent. If equipped with handrails, use them while climbing.
6. Do not climb on anything other than perforated steel steps.
7. To roll ladder again-
  - On models with spring casters, ladder is ready to roll when dismounted.
  - On models with locking device, step on pedal located under bottom step to place ladder in rolling position.

### Proper Care And Storage

1. Never store materials on ladder.
2. Never drop or apply an impact load to ladder.
3. Ladder can be disassembled for transport and storage.

# MINI FORTRUSS® MOBILE WORK STAND SM SERIES




### Center Locking Hinge

Employs a springloaded, locking pin, which automatically locks center hinge tubes in place.



### Two-Way Casters

Four positive locking, ball bearing casters provide a stable base. Non-marring casters have a quick release feature and are lock threaded into steel inserts in the scaffold's legs to reduce unit wobble.



### Exclusive Steel Wrap Weld Connection

Increases strength and durability.



### Premium Powder Paint

Baked on finish is durable and provides superior scratch and scuff resistance. Attractive, even coverage with no drips or runs.



### Storage

Folds easily for storage and transport.

### SPECIFICATIONS

**Adjustable Height:** The working height can be adjusted to 12", 24", 36", and 48".

**Ample Work Capacity:** Provides a large 17" x 43" work surface, along with 500 lbs. distributed load work capacity.

**End Frame Stops:** Exclusive non-pinching stops limit rotation of end frame to 90°.



Patent #5,555,954

### SM REPLACEMENT PARTS

ITEM NUMBER	DESCRIPTION
921010	Caster
396800A	Steel Plank

MODEL	CASTERS	WEIGHT	OVERALL LENGTH W/CASTERS	OVERALL HEIGHT W/CASTERS	OVERALL WIDTH	FOLDED UNIT WIDTH	PLANK WIDTH	PLANK LENGTH	PLANK HEIGHT ADJUSTABLE	LOAD RATING
SM1404A	4	68	47-1/2"	50-3/4"	22-1/2"	6-1/4"	8.5 (2) 17 overall	46-5/16"	12", 24", 36", & 48"	500lbs.