

HEAVY DUTY STEEL ROLLING WAREHOUSE LADDERS

GSX2400 SERIES (Knocked Down)

ALL SIZES MEET OR EXCEED THE REQUIREMENTS OF ANSI A14.7 AND OSHA 1910.29 STANDARDS WITH A

350 lbs. load capacity*

GSX2409 with option #X09 shown



ANSI A14.7
Meets or exceeds requirements of American National Standards Institute


OSHA REQUIREMENTS



Forward Descent
50 degree climbing angle meets ANSI requirements for forward descent.




Tubular Construction
Massive 2" x 1" rectangular tubing base designed to reduce abusive damage.



Wide Steps
The 17" top step and large 8-1/2" steps make climbing and working easier.




Handrail & Guardrail
All units come standard with 1-1/16" OD high strength steel tube handrails and guardrails.




Handrail & Outrigger (accessory)
Required when local codes require 3:1 height to base ratio.
4-9 Step GECAL0509-O
10-12 Step GRCAL1012-O
13-15 Step GRCAL1315-O

Super heavy duty ladders constructed for the most demanding requirements. Large ball bearing casters facilitate easy maneuvering. All models equipped with large swivel caster in front and rigid casters in the rear. Step on bottom step to activate and lock rubber tipped feet in down position. Step on unlocking pedal to unlock.



Bottom Landing Step
The 10" bottom step gives a larger surface to engage the locking mechanism.



Accessory: Unique Easy-Turn™ Design (#X09)
Louisville's exclusive Easy-Turn™ feature includes five strategically placed casters for easier mobility and maneuverability. The design allows the user to spin the entire platform on a dime.



Non Marring/Marking Casters
Each model is equipped with 4 ball bearing casters. The caster's material will not mark or mar the working surface.

NEW LLG MODEL	STEPS	STEP WIDTH	PLATFORM HEIGHT	OVERALL HEIGHT	OVERALL DEPTH	OVERALL WIDTH	APPROX. CUBE	WEIGHT
GSX2404	4	24"	40"	76"	49"	28"	14.6	113
GSX2405	5	24"	50"	86"	58"	28"	17.2	126
GSX2406	6	24"	60"	96"	66"	34"	19.8	146
GSX2407	7	24"	70"	106"	74"	34"	22.4	159
GSX2408	8	24"	80"	116"	82"	34"	25	200
GSX2409	9	24"	90"	126"	91"	34"	27.6	232
GSX2410	10	24"	100"	136"	99"	34"	30.2	248
GSX2411	11	24"	110"	146"	107"	34"	32.8	264
GSX2412	12	24"	120"	156"	116"	34"	35.4	280
GSX2413	13	24"	130"	166"	124"	39"	38	356
GSX2414	14	24"	140"	176"	133"	39"	40.6	369
GSX2415	15	24"	150"	186"	141"	39"	43.3	392

HEAVY DUTY STEEL ROLLING WAREHOUSE LADDERS

GSX1600 SERIES (Knocked Down)

ALL SIZES MEET OR EXCEED THE REQUIREMENTS OF ANSI A14.7 AND OSHA 1910.29 STANDARDS WITH A

350 lbs. load capacity*



Forward Descent
50 degree climbing angle meets ANSI requirements for forward descent.




Non Marring/Marking Casters
Each model is equipped with 4 ball bearing casters. The caster's material will not mark or mar the working surface.



Tubular Construction
Massive 2" x 1" rectangular tubing base designed to reduce abusive damage.



Bottom Landing Step
The 10" bottom step gives a larger surface to engage the locking mechanism.



Handrail & Outrigger (accessory)
Required when local codes require 3:1 height to base ratio.
3-7 Step
(16" Wide Only) GRCAL05EC-O

GSX REPLACEMENT PARTS

MODEL	DESCRIPTION	SIZE
999844A	Step Lock Spring	3'-15'
601054A	2" Rubber Pad	3'-15'
921004A	4" Swivel Caster	3'-7'
921007A	4" Rigid Caster w/Stud	3'-7'
921009A	5" Swivel Caster	8'-15'
921008A	5" Rigid Caster w/Stud	8'-15'

*GSX parts are not interchangeable with SX parts

NEW LLG MODEL	STEPS	STEP WIDTH	PLATFORM HEIGHT	OVERALL HEIGHT	OVERALL DEPTH	OVERALL WIDTH	APPROX. CUBE	WEIGHT
HANDRAILS								
GSX1603	3	16"	30"	66"	41"	23"	9.6	75
GSX1604	4	16"	40"	76"	49"	23"	11.7	91
GSX1605	5	16"	50"	86"	58"	23"	13.8	104
GSX1606	6	16"	60"	96"	66"	27"	15.8	118
GSX1607	7	16"	70"	106"	74"	27"	17.9	132

ANSI A14.7
Meets or exceeds requirements of American National Standards Institute

OSHA REQUIREMENTS